UN@HABITAT

Safe, Warm, Easy to build

Winter Shelter




How to Plan

This shelter can be made quickly.

Choose a site with protection from wind. Plan for the door to face the sun.

It is important to protect the shelter from aftershocks, cold and wind. Please carefully follow all the details shown below to make sure the shelter is safe and lasts for the winter.


Start by filling the sandbags so that the wall can be made.



Measure this size on ground. This is the inside of the wall. Mark each corner.



Check the diagonals to make sure the walls are straight.



Leave space each side for the roof poles.

Making the Walls






Lay the bags at and level, with no gaps.



Fold over the top of the bag.





Making the Roof



ber trusses.



Joints should be nailed and also tied with rubber or wire.



A ridge pole ties the trusses together and holds them in place



After the trusses are xed, cover the roof with shelter plastic.



Tie down the roof with rope or wire. The wire should be laid in wall from the base.



Fix 4 purlins for the CGI sheets. Sheets are 10 ft long.



Fix kera mats or other insulation between the purlins.



Fix shelter plastic at the gable. Insulate inside and x another sheet of plastic.



Fix CGI well against wind. Make sure roof poles are also well exed on the ground.

Fixing and Finishing



Do not nail plastic sheeting it may rip, always fold it and use a washer.



Fix the door in the wall with a steel strap.



Protect a stove with a reproof surround. Take care with fire in all tents and shelters.



Contact UN-Habitat, for information or advice:

Tel: (+92)(51) 8357358-8357363-64 | Fax: (+92)(51) 8357359 5th Floor, Serena Business Complex, Khayaban-e-Suhrawardy, Islamabad, Pakistan | Web: http://www.unhabitat.org.pk





